

INDUSTRIAL FLOORING



ANTI-SLIP FLOORING



PU FLOOR COATING



STAMPING CONCRETE



SELF LEVELLING FLOORING



FLOOR HARDENER



EPOXY FLOOR COATING

BUILD RITE
CONSTRUCTION CHEMICALS

Solutions for Professional Builders

INDUSTRIAL FLOORING

FLOORMASTER FC

Epoxy Floor Coating

FLOORMASTER FC is a two component, polyamide cured epoxy glossed floor coating formulated from carefully selected, highest grade epoxy resin and curing agent manufactured under strict quality control standards. The cured film forms a hard but flexible coating with excellent adhesion to clean concrete, steel and wooden surfaces with impervious finish which is easily cleaned.

Recommended for:

- Storage tanks
- Marine vessel and structures
- Equipment for mining, chemical, textile, food, power, fertilizer, sugar and others
- Production areas
- Warehouses
- Gasoline station and others

Packaging: Available in 4 lts set. (3 lts base and 1 ltr catalyst)

FLOORMASTER HARDENER DF

Dust Proofer, Surface Hardener and Sealing Compound for Concrete Floor

FLOORMASTER HARDENER DF is a single pack, concrete surface dust proofer and hardener for new and old concrete floors. **FLOORMASTER HARDENER DF** is based on sodium silicate, when applied to concrete reacts chemically to produce hard, dust free finish. It is supplied as a clear liquid ready for use direct from the container.

Recommended for:

- Ideal for dust proofing warehouses, car parks, garages, industrial plants and shopping malls.

Packaging: Available in 20 liter and 210 liter drums.

FLOORMASTER HARDENER NM

Non metallic surface hardener

FLOORMASTER HARDENER NM is a pre-mixed, non metallic, ready to use product. It is designed to be applied as a dry shake over freshly floated concrete to provide a hard wearing and durable monolithic floor.

FLOORMASTER HARDENER NM contains hard wearing graded aggregates, portland cement and other proprietary ingredients to improve workability.

FLOORMASTER HARDENER NM is available in natural (concrete gray) color as standard. Special colors will be produced on request for large orders.

Recommended for:

- Factories
- Showrooms
- Loading bays
- Repair workshops
- Warehouses
- Industrial and commercial floor surface subject to heavy traffic and severe impact

Packaging: Package ready-to- use in 25 kg moisture resistant bags. No mixing of ingredients is required at the job site.

FLOORMASTER FS ACR

Concrete Acrylic Sealer

FLOORMASTER FS ACR is a single pack, clear or pigmented penetrating synthetic acrylic sealer specially formulated from thermoplastic acrylic resin dispersed in a mixture of aromatic organic solvents. It is made in a brushable and sprayable consistency as sealer for concrete surfaces. Excellent adhesion to dry surfaces of concrete exhibits good alkalis and water resistance property. Sealing properties does not change even when the product is exposed to temperature of 20 oC and 100 oC, or when subjected to UV at the same time.

It is supplied and available in a range of colors ready to use direct from the container. When cured, forms a gloss to high gloss film.

It is also available in a clear and colorless liquid ideal as a clear top coat with outdoor exposure on concrete which forms a gloss to high gloss finished.

Matte finish is also available upon request.

Recommended for:

- Ideal for dust proofing warehouses, car parks, garages, walkways, concrete pavements and industrial buildings.
- As clear topcoat on concrete with outdoor exposure.

Packaging: Available in 1 gal and 16 liter tins.

FLOORMASTER SLS

Self-leveling, self-smoothing compound

FLOORMASTER SLS is a ready-to-mix self leveling mortar. It is used for leveling out rough and uneven floor surfaces prior to the application of floor finishes e.g. tiles, carpet, linoleum, rubber and other sheet flooring.

FLOORMASTER SLS contains a combination of especially selected cements, graded aggregates, synthetic polymers and a unique set control system. It requires only the addition of measured quantity of water to produce a smooth free flowing and self leveling material which can be applied 1 – 10mm in one application.

Recommended for:

- Interior floors for houses and buildings prior to the application of covering materials.

Packaging:

FLOORMASTER SLS : 25 kg PE bags
CONFIXCRETE ACR : 4 and 25 liter pail

FLOORMASTER SLS-OL

Self-leveling, self-smoothing compound

FLOORMASTER SLS-OL is a ready-to-mix self leveling mortar. It is used for leveling out rough and uneven floor surfaces for trafficable cementitious floors (overlayment) for new and reinstatement applications.

FLOORMASTER SLS-OL contains a combination of especially selected cements, graded aggregates, synthetic polymers and a unique set control system. It requires only the addition of measured quantity of water to produce a smooth free flowing and self leveling material which can be applied 3 – 15mm in one application.

Recommended for:

- Interior and exterior floors for houses, buildings and warehouses.

Packaging:

FLOORMASTER SLS-OL : 25 kg bag
ACRICOTE W40 : 4 and 25 liter pail

FLOOR GRIP

Anti-Slip Floor Treatment

FLOOR GRIP is tile floor treatment that increases floors coefficient of friction by up to 500% without changing the appearance or feel of the tile flooring.

FLOOR GRIP works on all ceramic, porcelain and mosaic tiles making them slip resistant especially when wet. It is supplied as a ready to use liquid. It is so effective that you can walk on a treated tile floor without slipping.

Recommended for:

FLOOR GRIP is recommended for slippery:

- Shower rooms
- Bathrooms
- Porcelain bathtubs
- And other floor tiles that require solution to "slippery when wet" problem

Packaging: Available in 1 liter and 4 liters plastic container.

FLOORMASTER HARDENER NM

Non-metallic surface hardener

FLOORMASTER PU

PU Floor Coating

FLOORMASTER FCH

FLOORMASTER SL H

Distributed by:

MAGNA PRIME DISTRIBUTION CORPORATION

#30 Kapiligan St., Brgy., Doña Imelda, Quezon City

Tel: (+632) 715-8130 to 32 | Fax: (+632) 715-8133



Solutions for Professional Builders